



Product Specification Data



Description

Briteline® IM3201 is a 3.4 mil. matte white intermediate calendered vinyl with permanent clear adhesive and 90# polycoated liner. Compatible with a variety of solvent, eco-solvent, latex and UV curable inks common to wide format digital printing systems.

Applications

Great for flat and simple curves - restricted to non-spill areas. Also recommended for POP, Product ID labels, OEM decals, outdoor and general signage.

Thickness

Film	3.4 mil
Adhesive	6.9 ± .6 mil

Dimensional Stability

Good

Surface Gloss

n/a

Recommendations

Allow printed media a minimum of 24 hours drying time prior to additional handling, finishing or laminating with solvent and eco-solvent inks.

Adhesion

15 min Permanent 3.5 lb/in (560 N/m)

Temperature Ranges

Minimum application temperature is 50°F.
Service temperature range is -40°F to 180°F.

Expected Exterior Exposure

5 years unprinted – depending on application area, purpose, exposure to the elements and vertical vs. horizontal installation.

Storage Stability

1 year shelf life when stored at temperatures below 23° C (73° F) and 50% relative humidity.

Product Series

IM3201-30	Matte 30" x 150'
IM3201-54	Matte 54" x 150'
IM3201-60	Matte 60" x 150'

Statement of Practical Use

We believe the information on this product to be accurate. However, since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied. The purchaser should refer to Grimco, Inc's price list for terms and conditions of sale, including disclaimer of warranties and limitation of liability.