



# Product Specification Data



## Description

BriteLine OLFL-311 overlamine is a polished flexible 6mil calendared gloss film with a slight emboss designed to be used as a protective overlay on floor decals and graphics.

## Applications

This laminate is intended to offer a slip resistant protective layer on floor graphics.

## Thickness

Film	6 mil
Adhesive	1 mil
Liner	4 mil

## Slip Resistance

OLFL-31154 is classified UL 410 for floor graphics overlay applications

## Water Resistance

Excellent

## Humidity Resistance

Excellent

## Temperature Ranges

Minimum application temperature	40°F
Service temperature range	-40°F to 200°F

## Expected Exterior Durability

This product is designed for indoor applications

## Expected Indoor Durability

OLFL-311 will function as a floor overlamine for 6 months under normal conditions

## Shelf Life

12 months shelf life when stored at 70°F and 50% relative humidity

## Product Series

OLFL-31154 54" x 150'

### Statement of Practical Use

We believe the information on this product to be accurate. However, since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied. The purchaser should refer to Grimco, Inc's price list for terms and conditions of sale, including disclaimer of warranties and limitation of liability.